

Geophysical Survey Systems, Inc.

To Whom it May Concern:

This is to certify that electromagnetic radiation emissions from transducers (antenna with transmitting and receiving electronics) manufactured by Geophysical Survey Systems, Inc. (GSSI) DO NOT constitute a safety or health hazard to operating personnel.

Emissions from GSSI transducers are far below the 10mW/cm² (100W/m²) level specified by the United States Occupational Safety and Health Administration (OSHA) regulations.

Paragraph 1910.97 states: "For normal environmental conditions and for incident electromagnetic frequencies from 100 MHz to 100 GHz, the radiation protection guide is 10 mW/cm² (milliwatt per square centimeter) as averaged over any possible 0.1 hour period."

Emissions data using GPR SIR® System 10, SIR® 2, SIR® 3, SIR® 4, SIR® 8, SIR® 20, SIR® 2000, SIR® 3000, SIR® 30 and SIR® 4000 (at the standard Pulse Repetition Frequency of 100 KHz) with the antenna Models listed and levels of Electromagnetic Radiation are specified herein:

Following is the average power density data at 5cm and wide band.

Antenna (MHz)	Average Power Density (W/m² @ 5 CM)	OSHA Spec. (W/m²)
100	Less than 0.0001	100
200	Less than 0.0001	100
300	Less than 0.0001	100
270	Less than 0.0001	100
400	Less than 0.0001	100
900	Less than 0.0001	100
1000	Less than 0.0001	100
1600	Less than 0.0001	100
2600	Less than 0.0001	100
Terravision	Less than 0.0001	100

John Rudy Vice President, Engineering Geophysical Survey Systems, Inc.

Form Name: OSHA Certificate

Form #: 7002.00 Revision #: Created: 10.24.2014 Revised: